

2024 Walnut Hill Special Cuts Open



Oil Pattern Distance **Forward Oil Total Tank Configuration**

41 11.655 mL **A Only**

Reverse Brush Drop Reverse Oil Total Tank A Conditioner

38 12.825 mL **ICE** Oil Per Board **Volume Oil Total Tank B Conditioner**

45 ul 24.48 mL **FIRE**

	START	STOP	LOADS	MICS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	1	45	14	37	0.0	0.0	0.0	1665
2	4L	4R	1	45	14	33	0.0	1.9	1.9	1485
3	8L	8R	3	45	14	75	1.9	7.8	5.9	3375
4	10L	10R	3	45	14	63	7.8	13.7	5.9	2835
5	12L	12R	3	45	18	51	13.7	21.3	7.6	2295
6	2L	2R	0	45	18	0	21.3	41.0	19.7	0

1 2L 2R 0 45 26 0 41.0 33.0 -8.0 2 11L 11R 3 45 22 57 33.0 23.7 -9.3 250 3 9L 9R 3 45 18 69 23.7 16.1 -7.6 310 4 7L 7R 2 45 14 54 16.1 12.2 -3.9 245 5 5L 5R 1 45 14 31 12.2 10.3 -1.9 135 6 2L 2R 2 45 14 74 10.3 6.4 -3.9 333
3 9L 9R 3 45 18 69 23.7 16.1 -7.6 310 4 7L 7R 2 45 14 54 16.1 12.2 -3.9 243 5 5L 5R 1 45 14 31 12.2 10.3 -1.9 133
4 7L 7R 2 45 14 54 16.1 12.2 -3.9 245 5L 5R 1 45 14 31 12.2 10.3 -1.9 135
5 5L 5R 1 45 14 31 12.2 10.3 -1.9 139
6 2L 2R 2 45 14 74 10.3 6.4 -3.9 33
7 2L 2R 0 45 14 0 6.4 0.0 -6.4

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

NA NA NA Forward Reverse Combined



ltem	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
item	SL-/L. IOL-ION	0L-12L.10L-10N	ISL-1/L. IOL-TOR	10L-10N.1/N-13N	10L-10N.12N-0N	10L-10N./N-3N
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	4.58	1.38	1	1	1.38	4.58



